MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION Identity (As Used on Label and List): Roll-On 340 Blue	SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION
Product Class: Skate Floor Finish	Respiratory Protection (Specify Types): Not normally required
Emergency Telephone Number: 800-255-3924	Ventilation: Local Exhaust: Not required Special: Not required
Telephone Number for Information: 817-571-2438	Mechanical (General): Ventilate to maintain vapor level below TLV & PEL (listed in
Distributor's Name and Address:	Section XI) Other: Not required Protective Gloves: Natural rubber or synthetic.
Roll-on Floor Systems, LLC 1001 South Main Street	Eye Protection: Approved safety goggles or glasses. Footwear: Not required
Euless, Texas 76040	Other Protective Clothing or Equipment: Not required
SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS	Work/Hygienic Practices: Do not use in food handling or storage areas when food
Hazardous Components (Specific Chemical Identity):	is present.
Chemical Common Name(s) %	SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS
A Mineral spirits 5 - 15 CAS #8052-41-3	Boiling Point: Mineral spirits 232-390°F (162-199°C) pH: N. Ap. Specific Gravity (H20) = 1: .973 % Volatile: < 50
B Tung oil 10 - 30	Vapor Density (Air = 1): > 1 Odor Threshold: N. Av.
CAS #8001-20-5	Evaporation Rate (Butyl Acetate = 1): < 1 Oil/Water Distribution
C Phenolic resin 10 - 30	Solubility in Water: Negligible Coefficient: N. Av.
CAS #54579-44-1	Vapor Pressure (MM HG): N. Av.
D Tert Butyl Acetate 5 - 15 CAS #540-88-5	Melting Point: N. Ap.
E Parachlorobenzotrifluoride 10 - 30	SECTION X - STABILITY AND REACTIVITY Stability: Unstable: Stable: X
CAS #98-56-6	Conditions to Avoid: N. Ap.
F Titanium Dioxide 10 – 20	Incompatibility (materials to avoid): Strong oxidizers
CAS #13463-67-7	Hazardous Decomposition or By-products: N. Av.
	Hazardous Polymerization: May occur: Will not occur: X
SECTION III - HAZARDS IDENTIFICATION	Conditions to Avoid: N. Ap.
Emergency Overview Appearance and Odor: Blue liquid, solvent odor.	SECTION XI - TOXICOLOGICAL INFORMATION
Primary Hazards: Harmful or fatal if swallowed. Vapor may be harmful.	Chemical OSHA PEL ACGIH TLV Recom. LD50 LC50
Flammable. Irritant.	A 500 ppm N/A N/A. 5000 mg/kg 5.5 mg/L (rat, oral) (4 hrs.)
Potential Health Hazards	B None None N/A None None
Route(s) of Entry: Skin Absorption: X Ingestion: Inhalation: X	
Eye: May cause irritation on contact. Skin: May cause irritation on contact.	C 0.5 ppm 0.3 ppm N. Av. N/A N/A
Ingestion: May be harmful if swallowed.	D 200 ppm N/A N/A. 4500 mg/kg. 3046 mg/kg
Inhalation: Vapor may be harmful.	(rat oral) (rat oral)
Signs and Symptoms of Exposure: Eyes and Skin: Irritation, redness. Inhalation:	
Irritation, central nervous system effects (dizziness, headaches, nausea, etc.).	E N/A. N/A N/A. 6800 mg/kg. 13.5 mg/L
Carcinogenicity: NTP? No IARC Monographs? No	(rat oral) (rat)
OSHA Regulated? No Terret Oren (a). Skin aver liver kidneye kumbaid avetem reenisters avetem and	
Target Organ (s): Skin, eyes, liver, kidneys, lymphoid system, respiratory system and central nervous system.	F N Ap. N. Ap. N.Ap. 13,000mg/kg N. Av. (rat, oral)
Medical Conditions Generally Aggravated by Exposure: Skin and respiratory	Teratogen, Mutagen, Reproductive Toxin Status: No
(asthma-like) conditions.	Toxicologically Synergistic Products: N. Av.
Health Hazards, Chronic: Reports have associated repeated or prolonged occupational	SECTION XII - ECOLOGICAL INFORMATION
exposure to solvents with permanent brain and central nervous system damage	Ecotoxicological Information: N. Av.
(sometimes referred to as Solvent or Painters Syndrome). Overexposure may cause	Chemical Fate Information: N. Av.
damage to one or more of target organs. SECTION IV - FIRST AID MEASURES	SECTION XIII - DISPOSAL CONSIDERATIONS
Emergency and First Aid Procedures:	Waste Disposal Method:
If Swallowed: Do not induce vomiting. Call a physician immediately. Eye Contact:	Dispose of spilled material in accordance with local, state and federal regulation (Incineration in an EPA authorized site is recommended)
Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical	RCRA Hazard Class: D001, Characteristic flammable
attention. Skin Contact: Flush thoroughly with cool water. Remove and wash	SECTION XIV - TRANSPORT INFORMATION
contaminated clothing before reuse. Inhalation: If ill effects occur from breathing vapors,	Shipping Classification: paint (class 3.3)
remove victim to fresh air and quiet and keep warm. Sources Used: Raw material data, general toxicology from the trade for similar	UN Number: 1263
products.	Packing Group: III
SECTION V - FIRE FIGHTING MEASURES	SECTION XV - PREPARATION DATA
Flammability: Flammable Autoignition Temperature: N. Ap.	Prepared By: Ron Camp
Flash Point (method used): 95°F (40°C) PMcc	Telephone Number: 651-414-3338
Flammable Limits: N. Av. LEL .7% UEL 10.%	Date: 08-2011 SECTION XVI - REGULATORY INFORMATION
Extinguishing Media	US Federal Regulations
Water? Foam? X Water Fog? X Alcohol Foam? CO2? X Dry Chemical? X	TSCA Status: All ingredients listed.
Vaporizing Liguid? X Other?	CERCLA Reportable Quality: None
Special Fire Fighting Procedures: Exclude air. Water hose stream may spread fire.	SARA Title III
Use water spray to keep containers cool.	Section 302 Extremely Hazardous Chemicals: None
Unusual Fire and Explosion Hazards: N. Av.	Section 311/312 Hazard Category: Immediate health, chronic health, fire.
TDG Flammability Classification: Not known	State Regulations NOTICE STATE OF CALIFORNIA
Sensitivity to Mechanical Impact: None Sensitivity to Static Discharge: Normal for flormable liquid	Warning: This product may contain chemicals known to the State of California to caus
Sensitivity to Static Discharge: Normal, for flammable liquid. SECTION VI - ACCIDENTAL RELEASE MEASURES	cancer or reproductive defects as trace impurities in the standard industrial materia
SECTION VI - ACCIDENTAL RELEASE MEASURES Steps to be Taken in Case Material is Released or Spilled:	used in the manufacture of this product.
Extinguish all sources of possible ignition (flames, sparks, pilot lights, etc.) and provide	International Regulations
ventilation. Dike and contain spill with inert material (sand, earth, etc.). Collect spill with	WHMIS Controlled Product Hazard Class: B2
absorbent material (example: floor-dri). Wash affected area with soap and water.	SECTION XVII - OTHER INFORMATION
SECTION VII - HANDLING AND STORAGE	None
Precautions to be Taken in Handling and Storing:	N. Ap Not Applicable; N. Av Not Available
Normal care in handling and storage. Do not store near heat or open flame.	
Other Precautions: Keep out of reach of children.	NFPA SYSTEM
	<u>2</u> A. Health Hazard <u>3</u> A. Fire Hazard <u>0</u> A. Reactivity Hazard

_2_A. Health Hazard _3_A. Fire Hazard _0_A. Reactivity Hazard THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.