MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

	00000000000						
SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION Identity (As Used on Label and List): Roll-On 340 Clear	SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION						
Product Class: Skate Floor Finish		Respiratory Protection (Specify Types): Not normally required Ventilation: Local Exhaust: Not required Special: Not required Mechanical (General): Ventilate to maintain vapor level below TLV & PEL (listed in					
Emergency Telephone Number: 800-255-3924							
Telephone Number for Information: 817-571-2438						,	
Distributor's Name and Address:							
Roll-on Floor Systems, LLC 1001 South Main Street		Eye Protection: Approved safety goggles or glasses. Footwear: Not required Other Protective Clothing or Equipment: Not required					
Euless, Texas 76040						areas when food	
SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS	Work/Hygienic Practices: Do not use in food handling or storage areas when food is present.						
Hazardous Components (Specific Chemical Identity):	SECTION IN			CHARACT	EDISTICS		
Chemical Common Name(s) %	SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point: Mineral spirits 232-390°F (162-199°C) pH: N. Ap.						
A Mineral spirits 5 - 15 CAS #8052-41-3	Specific Gravity (H20) = 1: .868 % Volatile: < 50						
B Tung oil 10 - 30	Vapor Density (Air = 1): > 1 Odor Threshold: N. Av.						
CAS #8001-20-5			I Acetate = 1)	: <1		er Distribution	
C Phenolic resin 10 - 30	Solubility in	Water: N	legligible		c	oefficient: N. Av.	
CAS #54579-44-1 D Tert Butvl Acetate 5 - 15	Vapor Pressure (MM HG): N. Av. Melting Point: N. Ap.						
D Tert Butyl Acetate 5 - 15 CAS #540-88-5							
E Parachlorobenzotrifluoride 10 - 30	-		Y AND REACT				
CAS #98-56-6	Stability: Unstable: Stable: X Conditions to Avoid: N. Ap.						
SECTION III - HAZARDS IDENTIFICATION			als to avoid):	Strong ox	ridizers		
Emergency Overview			ion or By-pro				
Appearance and Odor: Amber liquid, solvent odor.	Hazardous	Polymerizat	ion: M	ay occur:		toccur: X	
Primary Hazards: Harmful or fatal if swallowed. Vapor may be harmful. Flammable.	Conditions	to Avoid:	N. Ap.				
Irritant. Potential Health Hazards	SECTION X	- TOXICOL	OGICAL INFO	RMATION			
Route(s) of Entry: Skin Absorption: X Ingestion: Inhalation: X			ACGIH TLV		LD50	LC50	
Eye: May cause irritation on contact.	A	500 ppm	N/A	N/A.	5000 mg/kg	5.5 mg/L	
Skin: May cause irritation on contact.		None	Nana	(rat, oral)	(4 hrs.)	Nana	
Ingestion: May be harmful if swallowed.	В	None	None	N/A	None	None	
Inhalation: Vapor may be harmful.	С	0.5 ppm	0.3 ppm	N. Av.	N/A	N/A	
Signs and Symptoms of Exposure: Eyes and Skin: Irritation, redness. Inhalation: Irritation, central nervous system effects (dizziness, headaches, nausea, etc.).		••• FF	••• pp				
Carcinogenicity: NTP? No IARC Monographs? No	D	200 ppm	N/A	N/A.	4500 mg/kg.	13.5 mg/L	
OSHA Regulated? No					(rat oral)	(rainbow trout)	
Target Organ (s): Skin, eyes, liver, kidneys, lymphoid system, respiratory system and	Е	N/A.	N/A	N/A.	6800 mg/kg.	13.5 mg/L	
central nervous system.	-	1.1/7.	1.077	1.1/7.1.	(rat oral)	(rat)	
Medical Conditions Generally Aggravated by Exposure: Skin and respiratory (asthma-like) conditions.					,		
Health Hazards, Chronic: Reports have associated repeated or prolonged occupational			eproductive T		s: No		
exposure to solvents with permanent brain and central nervous system damage	Toxicologic	ally Synerg	istic Products	s: N. Av.			
(sometimes referred to as Solvent or Painters Syndrome). Overexposure may cause	SECTION XII - ECOLOGICAL INFORMATION Ecotoxicological Information: N. Av.						
damage to one or more of target organs.							
SECTION IV - FIRST AID MEASURES	Chemical Fa	ate Informat	ion: N. Av.				
Emergency and First Aid Procedures:	SECTION X	II - DISPOS	AL CONSIDE	RATIONS			
If Swallowed: Do not induce vomiting. Call a physician immediately. Eye Contact:	ning water for at least 15 minutes. If irritation persists, obtain medical Dispose of spilled material in accordance with local, state and federal regulation						
Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash							
contaminated clothing before reuse. Inhalation: If ill effects occur from breathing vapors,	PA authorized site is recommended)						
remove victim to fresh air and guiet and keep warm.	quiet and keen worm						
Sources Used: Raw material data, general toxicology from the trade for similar	SECTION XIV - TRANSPORT INFORMATION Shipping Classification: paint (class 3.3)						
products.	UN Number		- paint (UIdS	5 0.0)			
SECTION V - FIRE FIGHTING MEASURES	Packing Group: III						
Flammability: Flammable Auto ignition Temperature: N. Ap.	SECTION XV - PREPARATION DATA						
Flash Point (method used): 95°F (40°C) PMcc	Prepared By: Ron Camp						
Flammable Limits: N. Av. LEL .7% UEL 10.%	Telephone Number: 651-414-3338						
Extinguishing Media Water? Foam? X Water Fog? X	Date: 08-2011 SECTION XVI - REGULATORY INFORMATION						
Alcohol Foam? CO ₂ ? X Dry Chemical? X	US Federal Regulations						
Vaporizing Liquid? X Other?	TSCA Status: All ingredients listed.						
Special Fire Fighting Procedures: Exclude air. Water hose stream may spread fire.	CERCLA Reportable Quality: None						
Use water spray to keep containers cool.	SARA Title	SARA Title III Section 302 Extremely Hazardous Chemicals: None					
Unusual Fire and Explosion Hazards: N. Av. TDG Flammability Classification: Not known						boolth fire	
Sensitivity to Mechanical Impact: None	Section 311/312 Hazard Category: Immediate health, chronic health, fire. State Regulations						
Sensitivity to Static Discharge: Normal, for flammable liquid.	NOTICE STATE OF CALIFORNIA						
	Warning: Th	is product m	ay contain ch			of California to cause	
SECTION VI - ACCIDENTAL RELEASE MEASURES Steps to be Taken in Case Material is Released or Spilled:	cancer or reproductive defects as trace impurities in the standard industrial materials						
Extinguish all sources of possible ignition (flames, sparks, pilot lights, etc.) and provide	used in the manufacture of this product.						
ventilation. Dike and contain spill with inert material (sand, earth, etc.). Collect spill with							
absorbent material (example: floor-dri). Wash affected area with soap and water.							
SECTION VII - HANDLING AND STORAGE		VII - OTHER	INFORMATIC	ON			
Precautions to be Taken in Handling and Storing:	None						
Normal care in handling and storage. Do not store near heat or open flame.	N. Ap Not	Applicable;	N. Av Not /	Available			
Other Precautions: Keep out of reach of children.							
	NFPA SY	0					

NFPA SYSTEM <u>2</u> A. Health Hazard

<u>3</u> A. Fire Hazard <u>0</u>

<u>0</u> A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. WE ASSUME NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.