1. Identification

Product Identity: **Roll On Royal Blue** Recommended Use: Skate Floor Finish

Producer / Distributor

Roll-on Floor Systems, LLC 233 West Pipeline Road Hurst, Texas 76053

Telephone Number for Information: 817-571-2438 Emergency Telephone Number: 800-255-3924

2. **Hazard Identification**

Classification:

Health Class

Mild Skin Irritation Category 3 Eye Irritant Category 2 Skin Sensitizer Reproductive Toxicity Category 2 Specific Target Organ Toxicity Category 2



Physical Class

Flammable Liquid Category 3

Environment Class

Acute Aquatic Toxicity Category 2

Label



Signal Word Warning

Hazard Statements:

Causes eye and mild skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause damage to organs (central nervous system, lungs). Flammable liquid and vapor.

Precautionary Statements:

Wash hands thoroughly after handling. Avoid breathing dust/vapors. Contaminated work clothing should not be allowed out of the workplace. Wear protective clothing/eye protection. Do not handle until all safety precautions have been read and understood. Do not eat, drink, or smoke when using this product. Keep away from heat. No smoking. Keep container tightly closed. Use explosion-proof electrical/ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. If skin irritation or rash occurs; Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water. If exposed or concerned: Get medical attention. In case of fire: Use alcohol foam, CO2, dry chemical, water fog, or vaporizing liquid to extinguish.

Store locked up, in a well-ventilated place. Keep cool. Dispose of contents in accordance with local regulations.

. Composition/Information on Ingredients Ingredient	CAS Number	Percent by Weight
Mineral Spirits	8052-41-3	20 - 30
Tung Oil	8001-20-5	10 - 20
Phenolic Resin	54579-44-1	5 - 10
Linseed Oil	8001-26-1	5 - 10
Parachlorobenzotrifluoride	98-56-6	10 - 20
Tert-butyl Acetate	540-88-5	5 - 10
Pigment Dispersion	Proprietary	20 - 30

4.	 First-Aid Measures: Ingestion: If Swallowed: Do not induce vomiting. Call a physician immediately. Eye Contact: Flush eyes with running water for at least 15 minutes. Obtain immediate medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse. Inhalation: If ill effects occur from breathing vapors, remove to fresh air, keep warm and quiet and obtain medical attention. 				
5.	Fire Fighting Measures: Suitable Extinguishing Media: Foam - Water Fog - CO2 - Dry Chemical - Vaporizing liquid Special Fire Fighting Procedures: Water hose stream may spread fire, Use water spray to keep containers cool Unusual Fire and Explosion Hazards None are known				
6.	Accidental Release Measures: Extinguish all sources of possible ignition (flames, sparks, pilot lights, etc.) and provide ventilation. For large spills, dike and contain spill with inert material (sand, earth, etc.). Collect spill with absorbent material (example; floor-dry). For small spills, wipe up spill with mop or rag. Dispose of or treat mop or rag properly to avoid fire.				
7.	 Handling and Storage: Handling: Keep out of reach of children Storage: Do not store near heat sparks or flame. 				
8.	 Exposure Controls / Personal Protection: Exposure Limits Ingredients Mineral spirits Phenolic resin Tert Butyl Acetate Exposure Controls Engineering Controls: Ventilate to maintain vapor levels below endingering Controls: Ventilate to maintain vapor levels below endingering Controls: Ventilate to maintain vapor levels below endingering Controls: Approved Safety Goggles or Glasses Skin Protection: Approved Safety Goggles or Glasses Respiratory Protection: Not Required 	CAS Number 8052-41-3	Osha PEL 100 ppm	ACGIH TLV 100 ppm	
9.	Physical State:LiquidAppearance:BlueOdor:SolventSolubility:NegligibleEvaporation Rate:< 1	oH: NA Specific Gravity (H2O = 1): Flammability: Flammable Flash Point: 95°F (35°C) P Boiling Point: 232-390°F (1 %volatile: < 50%	Мсс		
10.	0. Stability and Reactivity: Chemical Stability: Stable Possibility of Hazardous Reactions: None are known Incompatability (Materials to Avoid): Strong Oxidizers Hazardous Decomposition or By-products: None Hazardous Polymerization: Will not Occur Conditions to Avoid: None are known				

Safety Data Sheet (SDS)

11. Toxicological Information:

Signs and Symptoms of Overexposure:

Causes irritation and redness to Eyes, and Skin or irritation upon inhalation, Dizziness, Headaches, and nausea.

	Acute Effects:		
	Eye Contact:	Causes irritation on contact	
	Skin Contact:	Causes mild irritation on contact	
	Inhalation:	Vapor may be harmful	
	Ingestion:	May be harmful if swallowed	
	Target Organ Effe	ects: Skin, Eyes, Respiratory system, Central Nervous System, Lymphoid System, Liver, Lungs, Kidneys and Suspected	
	Chronic Effects:	Reports have associated repeated or prolonged occupational exposure to solvents with permanent brain and central nervous system damage (sometimes referred to as Solvent or Painters Syndrome). Overexposure may cause damage to one or more of target organs.	
	Acute Toxicity Va	lues:	
	Oral LD ₅₀ > 5000 mg/kg		
	Dermal LD	0 ₅₀ > 5000 mg/kg	
	Inhalation	(Vapor) LC 50 > 50 mg/l	
12	Ecological Infor	mation.	

12. Ecological Information:

 Persistence and Degradability:
 Not Available

 Bio Accumulative Potential:
 Not Available

 Mobility in Soil:
 Not Available

 Aquatic Toxicity:
 Toxic to Aquatic Life

13. Disposal Considerations:

Material that cannot be used during normal use should be disposed of in accordance with all applicable local, state and federal regulations. Incineration in an EPA authorized site is recommended.

14. Transportation Information:

UN Number: UN1263 Shipping Name: Paint Transport Hazard Class: 3 Packing Group: III Marine Pollutant: NO

15. Regulatory Information:

 TSCA Status: All ingredients listed

 Clean Water Act: Tung Oil(8001-20-5) & Mineral Spirits(8052-41-3) are listed in the Clean Water Act as a Hazardous Substance.

 Clean Air Act: None of the chemicals in this product are listed under the CAA

 CERCLA Reportable Quantity: Tert Butyl Acetate (540-88-5), > 5000 lbs.

 SARA Title III Information:

 Section 302 Extremely Hazardous Chemicals: None Listed

 Section 311 / 312 Hazard Category: Immediate Health, Chronic Health, Fire

 Section 313 Toxic Chemicals: None Listed

 State Regulations: Notice State of California; Warning; This product may contain chemicals known to the state of California to cause cancer or reproductive defects as trace impurities in the standard industrial materials used in the manufacture of this product.

International Regulations: WHMIS Controlled Product Hazard Class: B2

16. Other Information:

Prepared By: Eric Scholl Telephone Number: 651-481-1900 Revision Date: 9/21/2017 Supersedes: 6/7/2013 This SDS applies to the following Part Numbers The information contained herein is based on data considered accurate; however no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The company assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

2

3

0

